

PRESTANDEKLARATION

Nr: 401

1	Produkttypens unika identifikationskod:		
	<ul style="list-style-type: none"> • Flügger Wet Seal, Wall Seal och All Seal • + artikelnummer och batch nummer på förpackningen 		
2	Avsedda användningar		
	<ul style="list-style-type: none"> • EN 15651 Fogmassa för användning inom och utomhus 		
3	Tillverkare:		
	<ul style="list-style-type: none"> • FLÜGGER Grönkullen SE-517 81 Bollebygd. www.flugger.se 		
4	Systemet eller systemen för bedömning och fortlöpande kontroll av byggproduktens prestanda enligt bilaga V:		
	<ul style="list-style-type: none"> • System 3 for reaction for fire 		
5	Harmoniserad standard		
	<ul style="list-style-type: none"> • EN 15651-1:2012 Sealants for non-structural use in joints in buildings and pedestrian walkways- • Part 1: Sealants for façade elements. • Part 2: Sealants for glazing • Part 3: Sealants for sanitary joints • • SKZ- TeCona A GmbH NB 1213 • IFT Rosenheim GmbH NB 0757 		
6	Angiven prestanda		
		Wet Seal	Wall Seal
		EN15651-1	EN15651-1
Type		F-EXT-INT	F-INT
Class		25LM	25HM
Reaction to fire		Class E	NPD
Release dangerous chemicals		NPD	NPD
Resistance to flow		≤ 3 mm	≤ 3 mm
Loss of volume		≤ 10%	NPD
Elongation at break		≥ 25%	≥ 25%
Tensile properties at maintained extension after water immersion			NF
Tensile properties (secant modulus) for use in cold climate areas (-30°C)			≤ 0,9 mPa
Tensile properties at maintained extension for use in cold climate areas (-30°C)			NF
Durability			Pass
		EN15651-2	
Type		G	
Class		25LM	
Elastic recovery		≥ 70 %	
Secant modulus at 23°C (N/mm ²)		≤ 0,4	
Secant modulus at -20°C (N/mm ²)		≤ 0,6	
Adhesion/cohesion after exposure to heat, water and artificial light		NF	
Resistance to compression (N/mm ²)		0,26	

	Wet Seal	Wall Seal	All Seal
	EN15651-3		
Type	S		
Class	XS1		
Tensile properties at maintained extension	NF		
Adhesion/cohesion at variable temperatures	NF		
Adhesion /cohesion at maintained extension after water immersion	NF		
Conditioning	Method A	Method A	Procedure B
Substrate	Aluminium	Aluminium	Mortar M1
	Mortar	Mortar	
	Glass		

7

Prestandan för ovanstående produkt överensstämmer med den angivna prestandan. Denna prestandadeklaration har utfärdats med förordning (EU) nr 305/2011 på eget ansvar av den tillverkare som anges ovan

Undertecknat för tillverkaren av:

Namn:

- **Anders Frisk**

Befattning:

- **R&D Specialist, Documentation**

Plats:

- **Bollebygd**

Dag: 2014.11.07

-

Namnteckning: