






Technical Data Sheet

Fiona construction wallpaper



Description:							
<p>Fiona construction collections meets the highest market demands regarding design as well as technical features. With a heritage of designing and producing wall paper since 1897 Fiona is one of the largest producer in Scandinavia and one of most modern in Europe.</p> <p>Fiona wallpaper represents highest technical level, with full opacity and washability far above average in market. Production site is one of the newest in Europe (2010), and certified according to ISO 14001. We use only waterborne ink and coating, no PVC by choice. Fiona wallpaper is printed on high quality non-woven backing with screen- and gravure printing technique, and has a very high grade of evenness in quality.</p> <p>Efficient for hanger: Roll length is 11,2 m. For rational hanging and maximum usage of roll. Always 4 lengths at standard walls, even if pattern match. Pattern match free or straight, never offset. No compromises in quality.</p>							
Application:							
<p>Applicable for covering in dry rooms. The substrate must be clean, dry and as well as solid. Slightly chalking or absorbent substrates shall be primed with sealer or pre-glued.</p> <p>Adhesive: Starch adhesive reinforced with PVA, suitable for non-woven wall paper. Adhesive shall be applied on the wall or at back of wallpaper in a uniform layer. 4-5 m² / liter is recommended for sufficient adhesion. If pasting the wall - leave the adhesive to dry on the wall for a while until it is "tacky".</p> <p>Hanging: Cut for edge-to-edge hanging. Smoothen lengths with a short napped smoothing brush or plastic smoother. Be careful when removing air pockets. Remove any excess of adhesive with a clean and rich moist sponge, and luke warm water, before it dries.</p>							
Technical data:							
			Weight per m²	Width	Roll length	Qty / box	Qty / pallet
			140 -180g	53cm ±3%	11,20m	12 roll	288 rolls
Valid collections		Stripes@HOME, Fioton Home NW, Fioton Living NW					
Washability			Extra washable, mat colours with mat acrylic top laquer				
Light fastness			Good light fastness				
Opacity			Full opacity. >99,5%				
Pattern match			Even light backgrounds cover different colored substrate Free or straight match, see each reference. Pattern repeat is marked on backside of wallpaper				
Periodic maintenance			Washable with damp cloth/sponge. Be careful when rubbing Wet removable				
CE approval	(EN 15102)	DoP 301	Certificate can be required				
RAL approval		479 / EN233	Certificate can be required				
Fire class	(EN 13501-1:2007)	B-s1,d0	Certificate can be required				
Emission TVOC	(ISO 16000)	A+	Certificate can be required				
HS number		48149010					
Production site			Flügger Sp. Z.o.o, Gdansk PL ISO 14001 certificate				

TDS FIONA CNW, version: December 2018

Always make sure that the Technical data sheet is the latest edition. Please also refer to the information provided on product label. All information is based on the existing legislation, laboratory tests and practical experience.

Contact: Flügger A/S, Islevdalvej 151, DK-2610 Rødovre. Denmark.

Phone +45 4454 1505. Mail: fionaexport@flugger.com

Fiona[®]
wall design