

Concrete Oil

Product properties

Flügger Concrete Oil is a transparent urethane alkydoil based dust binder for concrete floors indoor. The concrete oil gives the concrete floor a firm surface, improves cleaning and increases the wear resistance.



Product use

For dust binding of concrete floors where a durable surface, which withstands moisture and water impact, is desired. Particularly suitable for rooms with light to medium loads, e.g. a smaller warehouse, industrial premises, laundry room or garages.

A possible layer of concrete mud on new concrete floors should be removed by mechanical cleaning.

Substrate

Must be clean, dry, solid and suitable for surface treatment.

Application

Brush, roller or spraying.

Apply 2 thin and even coatings to avoid skin formation.

Environmental information

Remove as much paint as possible from brushes before cleaning. Do not pour residue/remains of paint down the drain, take it to your local recycling centre. Minimise your paint waste by calculating how much paint you need in advance. Store leftover paint properly so the remains can be reused, which minimises the environmental impact.

Storage

Cool, frost free and tightly closed

Protection equipment

Spray painting: painting suit, full face mask with combined filter. Painting: eye protection, gloves. Sanding: respiratory protection.

Technical Data

Product Type	Priming oil;Oilbased products
Density (kgs/l)	0.85
Solids Weight %	28
Solids Vol. %	23
Nominal spreading rate (m ² /ltr.)	8
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	4
Recoatable at 20° C, 60 % RH (Hours)	12
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	Do not dilute
Cleaning of Tools etc.	White spirit

Current TDS Version

October 2024

Replaces TDS Version

July 2020