

Interior Blackboard Finish

Properties

Flat, aqueous paint making it easy and practical to make beautiful and personal blackboards for information written with chalk.

- **Make a smart and very personal blackboard**
- **Wherever you want**
- **Easy to apply - fine adhesion to most substrates**



Treatment

The substrate must be clean, dry and solid. Remove chalking and loose paint. Clean with Fluren 37, Basic Cleaner before paint treatment. Prime untreated substrates with Flügger Interior Wood Primer. Prime metal with a rust-preventive priming paint.

Apply by paint brush, or by short-piled paint roller.

Apply 2 coats to obtain the best result. Let dry between the two applications.

Application

For interior use on wood and metal for substrates, where you want a surface looking and working like a blackboard.

Technical Data

Product Type	Acrylic paint
Gloss	3;Matte
Density (kgs/l)	1,3
Solids Weight %	53
Nominal spreading rate (m ² /ltr.)	10
Min. working temp. during application and drying/curing	Min. +5°C
Drying time at 20° C, 60 % RH (Hours)	2
Recoatable at 20° C, 60 % RH (Hours)	6
Dilution	Water, though normally not be diluted
Cleaning of tools:	Water and soap

Current TDS Version

November 2010

Replaces TDS Version

January 2009

