

Spray

Properties

Fast-drying spray primer that provides good adhesion. Provides protection against corrosion and can be painted over with all types of spray paint.

Use

Fast-drying acrylic primer for wood, metal, aluminium, glass and stone.

Substrate

Must be clean, dry, free of grease and suitable for surface treatment.

Treatment

Remove loose material and paint by cleaning and sanding.

Dirt, grime, grease and spills are removed by cleaning.

Sand hard, smooth surfaces.

After drying, sand the surface (grit 600).

Application

Shake for two minutes before use.

Test on small area to check adherence and the result.

Spraying distance 25 - 30 cm.

Working temperature 15 - 25°C.

Apply in several thin layers.

Drying time depends on air temperature, humidity and applied layer thickness.

After use, turn the can upside down and spray for several seconds.

Expected result

Matt, covered surface.

Can be sanded/sprayed over after 2 hours.

Finish with an opaque spray paint in the desired gloss and colour.

Environmental information

Clean off the paint from tools before cleaning. Bring remains of fluent paint to the local recycling centre. Minimize your paint waste by pre-estimating how much paint you need. Keep the leftover paint for future use so you can effectively reduce the environmental impact.

Storage: Cool, frost-free and tightly closed



Technical Data

Gloss	Matte
Solids Weight %	12.9
Min. working temp. during application and drying/curing	Min. +15°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	2
Fully cured at 20° C, 60 % RH (Days)	1

Current TDS Version

January 2022