

Natural Wood Stain

Product properties

Water-based stain for colouring untreated wood, indoors. Gives the wood a semi-matt colouration that is dirt-repellent and withstands light cleaning. Emphasises the grain and natural play of the wood. The colour shade may vary depending on the type of wood. The stained surface can subsequently be lacquered with water-based lacquer for a more robust surface.

- Colouring of untreated wood
- Dirt-repellent surface
- Semi-matt



Labelling



The product is a declared item in the Supply Chain Declaration Portal (SCDP) for New Buildings generation 4.

Product use

Used on e.g. furniture, panelling and floors where you want to give the wood a new colour. For light-coloured woods such as pine, spruce, beech and ash.

Substrate

Must be clean, dry, firm and suitable for surface treatment.

Treatment

Dust off new wood.

Sand off marks and stains.

Clean previously stained wood with Natural Wood Cleaner.

Wipe off with a firmly wrung cloth.

Application

Brush.

Stir thoroughly before and during use.

Apply in an even, thin layer along the length of the wood.

Avoid overlaps.

The wood stain must be worked into the wood.

If you need to apply a second coat, sand with fine sandpaper (grain size 120/180) and remove sanding dust.

Apply a maximum of 2 coats of wood stain on the same day.

Always carry out a test treatment to verify and accept the adhesion and result.

Expected result

Uniform stained surface.

Cleaning and maintenance

The surface can be gently cleaned with soapy water and a wrung-out cloth.
Maintenance is carried out as needed with Flügger Natural Wood Stain.

Environmental information

Remove as much paint as possible from tools before cleaning.
Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.
Empty and dry packaging should be sorted as plastic.

Storage

Cool, frost free and tightly closed

Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.
Avoid inhalation of spray mist and grinding dust.
Wear suitable protective equipment, see safety data sheet for further information.

Technical Data

Product Type	Wood stain
Gloss	20;Semi Matte
Density (kgs/l)	1.04
Solids Weight %	21
Solids Vol. %	19
Nominal spreading rate (m ² /ltr.)	15
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	4
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	Do not dilute
Cleaning of Tools etc.	Water and brush cleaner
Country of Origin	Denmark

Current TDS Version

March 2025

Replaces TDS Version

December 2024

